

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number
WO 2004/011743 A1

(51) International Patent Classification⁷: **E04H 4/16**

(21) International Application Number:
PCT/CZ2003/000035

(22) International Filing Date: 25 June 2003 (25.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PUV 2002-13339 25 July 2002 (25.07.2002) CZ

(71) Applicant (for all designated States except US): **STERBA, Miroslav** [CZ/CZ]; Taussigova 1172, 182 00 Praha 8 (CZ).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **NAVRATIL, Oldrich** [CZ/CZ]; Babylon c. 48, 345 06 Domazlice (CZ).

(74) Agents: **ANDERA, Jiri** et al.; Rott, Ruzicka & Guttman, P.O. Box 94, 170 00 Praha 7 (CZ).

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: VACUUM CLEANER FOR RESERVOIRS



(57) Abstract: A vacuum cleaner for reservoirs, especially swimming pools, comprising a working chamber (1) provided with an inlet (3) for liquid, connected with a vacuum generating unit (2). Between the inlet (3) of liquid and the vacuum generating unit (2) there is a rotary-shaped rolling rotor (4) placed in the flow of drawn in liquid. The rolling rotor (4) being arranged in swivelling and rotary manner and encompassed with a surface (5) for rolling. In the contact point between the rolling rotor (4) and the surface (5) for rolling the rolling rotor (4) has smaller diameter than the surface (5) for rolling. The rotor (4) is connected with at least one brush (6).

WO 2004/011743 A1

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Vacuum Cleaner for Reservoirs

Technical Field

The invention relates to a vacuum cleaner for reservoirs, especially swimming pools, comprising a working chamber provided with an inlet for liquid, connected with a vacuum generating unit.

Background Art

The known vacuum cleaners for reservoir, mainly the ones applicable to the leisure swimming pools, but also to those for the industrial purposes, including the firewater reservoirs, are either manual, semiautomatic, or automatic. The vacuum-cleaners are drawing in the dirt together with water which will bring them to the filter seated just inside the vacuum cleaner, or in the filtration system off the cleaned reservoir. In order that the vacuum cleaner could work, it must be connected to the pump being mostly situated outside the reservoir and providing the necessary vacuum.

The known manual vacuum cleaners consist of the working chamber open at its bottom and fitted optionally with the immovable brushes. A flexible hose is used to connect the working chamber with the vacuum generating unit. The working chamber is moved along the reservoir bottom or side walls with the bar affixed to it. The bar tends to be of a telescopic type.

The semiautomatic or fully automatic vacuum cleaners are moreover fitted with a mechanism which moves the working chamber along the reservoir bottom, sometimes also with a remote control.

The disadvantage of all known water reservoir vacuum cleaners is that the efficiency of the mechanical part of the cleaning depends only on the speed with which the brush is moved along the surface being cleaned and on the press down force.

For a perfect contact between the brush and the surface being cleaned it is good for the brush to be connected with the rotor via a swinging joint.

In its convenient embodiment the rotor has a shape of a hollow hemisphere with its open side facing the incoming flow and the brush arranged along the circumference edge of the hemisphere.

With the utmost simplification of the construction in mind it is advantageous to have the rolling rotor seated inside the working chamber and the rolling surface made directly on the inner wall of the working chamber.

In accordance with its other advantageous embodiments the working chamber has at its bottom edge a set of inlets for liquid, the working chamber can be connected with the vacuum generating unit with a flexible hose and a bar designed to move the cleaner can be attached to the working chamber.

For the reduced operating costs the brush can be fitted in a replaceable way.

Brief Description of Drawings

The invention will be described with the use of the schematic drawings where the Figures 1, 2, and 3 illustrate various examples of the vacuum cleaner. The Figure 4 gives an example as how to use the vacuum cleaner in a swimming pool. The Figure 5 shows an example of the rotor construction with a replaceable brush. The Figure 6 shows an example of the working chamber design.

Modes for Carrying Out the Invention

Figure 1 shows the first example of the vacuum cleaner designed to clean leisure swimming pools. The unit has a working chamber 1, open in its bottom part, while this opening forms an inlet 3 for liquid. At the upper end, there is the working chamber 1 connected with a vacuum generating unit 2 by means of a flexible hose 8.

A rolling liquid-operated machine, which can also be used to drive the rotating tools, is known from the published international patent applications No. WO 98/17910 and WO 99/61790, the disclosures of which are incorporated by references.

This machine consists of a chamber equipped with a liquid intake line and at least one outlet opening with the rolling rotor placed upstream the opening. The rolling rotor is of rotary-shaped body. A brush can be mounted on the output shaft. Such equipment can be used to clean the surfaces. In this case the dirt is disturbed mechanically with the rotating brush and flushed away by the liquid flowing out of the machine's chamber.

Goal of the invention is to design a liquid reservoir vacuum cleaner, which would make it possible to disturb mechanically the debris stuck to the reservoir's bottom and walls, using the rotating brushes, without the necessity to install any auxiliary power supply unit.

Disclosure of Invention

The above goal can be achieved with a vacuum cleaner designed to clean the liquid reservoirs, especially swimming pools, comprising a working chamber, which has an inlet for liquid, being connected with a vacuum generating unit. Between the liquid inlet and the vacuum generating unit there is a rotary shaped rolling rotor arranged in the flow of the liquid being drawn in. The rolling rotor is arranged both in inclinable and in rotary manner and encompassed with a surface for rolling. In the contact point between the rolling rotor and the surface for rolling the rolling rotor has smaller diameter than the surface for rolling. The rotor is connected with at least one brush.

The advantage of the vacuum cleaner pursuant to the invention rests in a substantially increased reservoir cleaning efficiency and quality, all this without the necessity to install any auxiliary power supply unit.

Vacuum generating unit 2 is formed by a pump installed in a circulation circuit, which is a part of technical equipments of the known swimming pools. These technical equipments are used to circulate water for its filtering and/or heating. In such an embodiment the vacuum cleaner uses a filter (not shown here) to capture the dirt. This filter forms a part of the known circulating circuit.

In another embodiment not shown here, the filter can be a part of the vacuum cleaner itself. Such a design is used to clean the liquid reservoirs or swimming pools without any circulating circuits. In such a case, any movable pump can be used as the vacuum generating unit 2.

In the case of the embodiment according to the Figure 1 the rolling rotor 4 is attached to a shaft 10, which is placed in the working chamber 1 in inclinable and in rotary manner. Various supports of the rotor 4 will not be described in detail since they have been described in the published international applications no. WO 98/17910 or WO 99/61790 the disclosures of which are incorporated by references.

The rolling rotor 4 can have any rotary shape, having a smaller diameter than the rolling surface 5 in the point where the rolling rotor 4 comes in contact with the rolling surface 5 created on the inner wall of the working chamber 1.

In the illustrated embodiment the rotor 4 is shaped like a hollow hemisphere with its open side upstream, with a brush 6 arranged along circumference edge of the hollow hemisphere. In the embodiment as per Figure 1 the bristles of the brush 6 are affixed straight in the edge of the rotor 4. An advantageous embodiment is shown in the Figure 5 where the brush 6 is attached to the rotor 4 in a removable way. Such an embodiment makes it possible to replace the worn brush 6.

For a perfect contact between the brush 6 and the surface being cleaned the design in the Figure 1 uses the rotor 4 affixed to the shaft 10 by means of the swinging joint 7.

A telescopic bar 9 is attached to the working chamber 1 in order to move the cleaner along the bottom and walls of the reservoir being cleaned.

When a swimming pool is to be cleaned, the working chamber 1 has to be connected with the vacuum generating unit 2, using the flexible hose 8. The cleaner is now lowered down into the pool with the bar 9 (see Figure 4). The water drawn in through the inlet 3 flows via the working chamber 1 to the filter (not shown here), coming in the filtered form back to the pool, using the line 11.

The water current flowing through the working chamber 1 will cause the rolling rotor 4 rolling along the inner wall of the working chamber 1. This principle has been described in the published international patent applications no. WO 98/17910 and WO99/61790 the disclosures of which are incorporated by references and will not therefore be analysed here in details. Along with the rotor 4, the brush 6 will stay in a precession.

Once the vacuum cleaner is connected to the swimming pool's circulation circuit with the a filtration and a pump with the capacity of 50 m^3 of the pumped water in an hour, the rotor 4 has an average speed of 100 rpm, exerting the micro-oscillations at the same time, 1,500 per minute on average. The micro-oscillations resulting from the rotor 4 rolling along the rolling surface 5 spread themselves up to the brush 6, using the shaft 10. The dirt is disrupted mechanically with the brush 6, being also flushed away with the flowing water via the working chamber 1 into the filter (not shown here) where the dirt is trapped and the clean water comes back to the swimming pool using the line 11. A surface of 15 m^2 can be cleaned well with the described device being moved just manually with the telescopic bar 9 in about 10 minutes. Of course, any other known driving device can be used to move the working chamber 1 along the surfaces being cleaned, including an automatic or remote control system.

Another embodiment of the vacuum cleaner is shown in the Figure 2. This embodiment differs from the one in Figure 1 in the rolling rotor 4 which is firmly attached to the shaft 10 and which has a separate brush 6 underneath. To be in

perfect contact with the surface being cleaned this brush 6 is attached to the rotor 4, using the swinging joint 7. The brush 6, of course, can be of a replaceable design.

The embodiment in Figure 3 is, in fact, the same as the one in Figure 2, except of the bottom edge of the working chamber 1, holding the immovable auxiliary brush 12.

Functionally, the embodiments in the Figures 2 and 3 is similar to the one described above in the Figure 1.

Embodiment according to Figure 6 has the inlet 3 of the working chamber 1 formed by a set of openings, made on the bottom edge of the working chamber 1.

In case of all the above-described embodiments the surface 5 for the rotor 4 rolling is created directly on the inner side of the working chamber 1. Such a design is simplest as far as the driving of the brush 6 is concerned. But this is not the only possible arrangement. The surface 5 for rolling and the rotor 4 can, in fact be, placed wherever in the flow of water drawn in.

The experts take it for granted that the described vacuum cleaner can be used not only to clean the swimming pools, but also, in fact, any reservoirs containing a liquid.

CLAIMS

1. A vacuum cleaner for reservoirs, especially swimming pools, comprising a working chamber (1) provided with an inlet (3) for liquid, connected with a vacuum generating unit (2), **characterized by the fact** that between the inlet (3) of liquid and the vacuum generating unit (2) there is a rotary-shaped rolling rotor (4) placed in the flow of drawn in liquid, the rolling rotor (4) being arranged in swivelling and rotary manner and encompassed with a surface (5) for rolling, while in the contact point between the rolling rotor (4) and the surface (5) for rolling the rolling rotor (4) has smaller diameter than the surface (5) for rolling, and the rotor (4) is connected with at least one brush (6).
2. The vacuum cleaner as in Claim 1, **wherein** the brush (6) is attached to the rotor (4) via a swinging joint (7).
3. The vacuum cleaner as in Claim 1, **wherein** the rotor (4) is shaped like a hollow hemisphere with its open side upstream, while the brush (6) is arranged along the circumference edge of the hollow hemisphere.
4. The vacuum cleaner as in any of the Claims 1 to 3, **wherein** the rolling rotor (4) is placed in the working chamber (1) and the surface (5) for rolling is formed on the inner wall of the working chamber (1).
5. The vacuum cleaner as in any of the Claims 1 to 4, **wherein** the working chamber (1) has at its bottom edge a set of the inlets (3) for liquid.
6. The vacuum cleaner as under any of the Claims 1 to 5, **wherein** the working chamber (1) is connected with the vacuum generating unit (2) with a flexible hose (8), while the bar (9) is attached to the working chamber (1) to move it.
7. The vacuum cleaner as in any of the Claims 1 to 6, **wherein** the brush (6) is fitted in a replaceable way.

1/3




Fig. 1




Fig. 2

2/3




Fig. 3




Fig. 4

3/3




Fig. 5




Fig. 6

INTERNATIONAL SEARCH REPORT

International application No
PCT/CZ 03/00035

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 E04H4/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 E04H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 799 351 A (FRENTZEL HERMAN E ET AL) 1 September 1998 (1998-09-01) column 4, line 53 -column 8, line 59; figures 1-9	1,3-7
A	US 5 044 034 A (IANNUCCI ANTHONY A) 3 September 1991 (1991-09-03) the whole document	1,4-7
A	EP 0 558 337 A (SEBOR PAVEL) 1 September 1993 (1993-09-01) column 9, line 1 -column 14, line 39; figures 1-11	1,4-7
A	EP 0 475 736 A (PEARCE RONALD JAMES) 18 March 1992 (1992-03-18) column 3, line 3 -column 7, line 18; figures 1-8	1,4-6
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

29 October 2003

Date of mailing of the international search report

04/11/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Stefanescu, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CZ 03/00035

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 99 61790 A (SEDLACEK MIROSLAV ;HOSTIN STANISLAV (SK)) 2 December 1999 (1999-12-02) cited in the application page 4, line 9 -page 8, line 11; figures 1-5</p> <p>-----</p>	1

INTERNATIONAL SEARCH REPORT

Internati... application No

PCT/CZ 03/00035

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 5799351	A	01-09-1998	US	5379473 A	10-01-1995
			US	5293659 A	15-03-1994
			AU	685529 B2	22-01-1998
			AU	8090994 A	23-05-1995
			BR	9407983 A	03-12-1996
			CA	2175364 A1	11-05-1995
			DE	69430135 D1	18-04-2002
			DE	69430135 T2	28-11-2002
			EP	0726998 A1	21-08-1996
			ES	2179852 T3	01-02-2003
			WO	9512730 A1	11-05-1995
			ZA	9408388 A	25-07-1996
			AU	686268 B2	05-02-1998
			AU	8091094 A	23-05-1995
			BR	9407948 A	26-11-1996
			CA	2175208 A1	11-05-1995
			DE	69425754 D1	05-10-2000
			DE	69425754 T2	19-04-2001
			EP	0726999 A1	21-08-1996
			ES	2153437 T3	01-03-2001
			WO	9512731 A1	11-05-1995
			ZA	9408386 A	27-06-1995
			US	5428854 A	04-07-1995
			AU	643831 B2	25-11-1993
			AU	8461291 A	26-03-1992
			BR	9104046 A	02-06-1992
			CA	2051936 A1	22-03-1992
			DE	69123524 D1	23-01-1997
			DE	69123524 T2	15-05-1997
			EP	0476413 A2	25-03-1992
			ES	2096607 T3	16-03-1997
			HK	1008060 A1	30-04-1999
			NZ	239886 A	26-08-1994
			ZA	9107026 A	27-05-1992
<hr/>					
US 5044034	A	03-09-1991	NONE		
<hr/>					
EP 0558337	A	01-09-1993	US	5404607 A	11-04-1995
			AU	663920 B2	26-10-1995
			AU	663921 B2	26-10-1995
			AU	3373793 A	02-09-1993
			BR	9300705 A	31-08-1993
			DE	69307358 D1	27-02-1997
			DE	69307358 T2	12-06-1997
			EP	0558337 A1	01-09-1993
			ES	2096201 T3	01-03-1997
			NZ	245991 A	26-07-1995
			US	5664275 A	09-09-1997
			US	5797156 A	25-08-1998
			US	5974647 A	02-11-1999
			CA	2090195 A1	29-08-1993
			US	5285547 A	15-02-1994
			ZA	9301377 A	23-09-1993
			US	5303444 A	19-04-1994
			US	5371910 A	13-12-1994
			ZA	9301380 A	21-10-1993
			US	5274868 A	04-01-1994
			ZA	9301378 A	23-09-1993

INTERNATIONAL SEARCH REPORT

International Application No
PCT/CZ 03/00035

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0558337 A		US 5386607 A	07-02-1995
		US 5261287 A	16-11-1993
		ZA 9301379 A	23-09-1993
		US 5259258 A	09-11-1993
		US 5259082 A	09-11-1993
EP 0475736 A	18-03-1992	AT 137296 T	15-05-1996
		AU 637934 B2	10-06-1993
		AU 8381991 A	19-03-1992
		DE 69119006 D1	30-05-1996
		DE 69119006 T2	12-06-1997
		EP 0475736 A1	18-03-1992
		ES 2087973 T3	01-08-1996
		US 5226205 A	13-07-1993
		ZA 9107219 A	27-05-1992
WO 9961790 A	02-12-1999	AU 3594099 A	13-12-1999
		BR 9910636 A	06-02-2001
		WO 9961790 A1	02-12-1999
		EP 1082538 A1	14-03-2001
		JP 2002516958 T	11-06-2002

PUB-NO: WO2004011743A1
DOCUMENT-IDENTIFIER: WO 2004011743 A1
TITLE: VACUUM CLEANER FOR
RESERVOIRS
PUBN-DATE: February 5, 2004

INVENTOR-INFORMATION:

NAME	COUNTRY
NAVRATIL, OLDRICH	CZ

ASSIGNEE-INFORMATION:

NAME	COUNTRY
STERBA MIROSLAV	CZ
NAVRATIL OLDRICH	CZ

APPL-NO: CZ00300035
APPL-DATE: June 25, 2003

PRIORITY-DATA: CZ200213339U (July 25, 2002)

INT-CL (IPC): E04H004/16

EUR-CL (EPC): E04H004/16

ABSTRACT:

CHG DATE=20040224 STATUS=O>A vacuum cleaner for reservoirs, especially swimming pools, comprising a working chamber (1) provided with an inlet (3)

for liquid, connected with a vacuum generating unit (2). Between the inlet (3) of liquid and the vacuum generating unit (2) there is a rotary-shaped rolling rotor (4) placed in the flow of drawn in liquid. The rolling rotor (4) being arranged in swivelling and rotary manner and encompassed with a surface (5) for rolling. In the contact point between the rolling rotor (4) and the surface (5) for rolling the rolling rotor (4) has smaller diameter than the surface (5) for rolling. The rotor (4) is connected with at least one brush (6).